

硬质合金光滑极限塞规(单头)




定制塞规
可定制其它等级, 如H8, H9, G7
可定制直径, 如19.003mm
可定制长度, 如70mm



6331-9C

- 符合JJG光滑极限量规国家计量检定规程
- 包含通规和止规



H7尺寸公差 (mm)					
直径(mm)	Ød1 通规尺寸公差(mm)	Ød2 止规尺寸公差(mm)	L1	L2	L
≥0.5, ≤3	+0.0010/+0.0022	+0.0088/ +0.010	20	15	95
>3, ≤6	+0.0013/+0.0027	+0.0106/+0.012	20	15	95
>6, ≤10	+0.0015/+0.0033	+0.0132/+0.015	20	15	95
>10, ≤15	+0.0018/+0.0038	+0.0160/+0.018	20	15	95
>15, ≤18	+0.0018/+0.0038	+0.0160/+0.018	20	15	115
>18, ≤30	+0.0023/+0.0046	+0.0186/+0.021	20	15	115
>30, ≤40	+0.0023/+0.0055	+0.0220/+0.025	20	15	115

H7

型号	直径(mm)
6331-1C*	1
6331-2C*	2
6331-3C*	3
6331-4C*	4
6331-5C*	5
6331-6C*	6
6331-7C*	7
6331-8C*	8
6331-9C*	9
6331-10C*	10
6331-11C*	11

型号	直径(mm)
6331-12C*	12
6331-13C*	13
6331-14C*	14
6331-15C*	15
6331-16C*	16
6331-17C*	17
6331-18C*	18
6331-19C*	19
6331-20C*	20
6331-21C*	21
6331-22C*	22

型号	直径(mm)
6331-23C*	23
6331-24C*	24
6331-25C*	25
6331-26C*	26
6331-27C*	27
6331-28C*	28
6331-29C*	29
6331-30C*	30
6331-31C*	31
6331-32C*	32
6331-33C*	33

型号	直径(mm)
6331-34C*	34
6331-35C*	35
6331-36C*	36
6331-37C*	37
6331-38C*	38
6331-39C*	39
6331-40C*	40

*带生产厂检验证书