

可定制

圆周尺


INSIZE PLUS

- 符合企业标准
- 用于测量管子、树和轮胎等的外径和外圆周长
- 激光刻线
- 不锈钢尺身




7115-3460

单位: mm



型号	圆周测量范围	直径测量范围	分度值	精度	
				圆周测量	直径测量
7115-950*	150-950mm	Ø50-300mm	0.1mm	±0.60mm	±0.20mm
7115-2200	940-2200mm	Ø300-700mm	0.1mm	±0.60mm	±0.20mm
7115-3460	2190-3460mm	Ø700-1100mm	0.1mm	±0.60mm	±0.20mm
7115-4720	3450-4720mm	Ø1100-1500mm	0.1mm	±0.90mm	±0.30mm
7115-5980	4710-5980mm	Ø1500-1900mm	0.1mm	±0.90mm	±0.30mm
7115-7230	5970-7230mm	Ø1900-2300mm	0.1mm	±1.05mm	±0.35mm
7115-8500	7220-8500mm	Ø2300-2700mm	0.1mm	±1.20mm	±0.40mm
7115-9760	8490-9760mm	Ø2700-3100mm	0.1mm	±1.35mm	±0.45mm
7115-11010	9730-11010mm	Ø3100-3500mm	0.1mm	±1.50mm	±0.50mm



* 当直径测量范围为Ø50-100mm时, 测量圆周的精度为±0.90mm, 测量直径的精度为±0.30mm.