



视频



ISF-S10



ISF-S500



ISF-S1000

- 符合弹簧拉压试验机国家机械行业标准
- 峰值保持及自动解除功能
- 上下限设定, 红绿灯指示灯及蜂鸣器报警
- 三种单位N、kgf、lbf自动转换
- 内置打印机
- 自动关机

技术参数

型号	ISF-S10	ISF-S20	ISF-S30	ISF-S50	ISF-S100	ISF-S200	ISF-S300	ISF-S500	ISF-S1000	ISF-S2000	ISF-S5000
最大载荷	10N	20N	30N	50N	100N	200N	300N	500N	1000N	2000N	5000N
分辨率	0.001N	0.002N	0.01N	0.01N	0.02N	0.05N	0.1N	0.1N	0.2N	0.5N	1N
位移标尺行程	65mm			95mm			150mm				
位移标尺分辨率	0.01mm			0.01mm			0.01mm				
压盘尺寸	Ø30mm			Ø49mm			Ø108mm				
弹簧最大自由长度	65mm			95mm			200mm				
力测量范围	5%~100%(最大载荷)										
力示值误差	±1%(最大载荷)										
输出接口	RS232										
电源	220V, 50/60Hz										
尺寸	300×235×600mm			300×235×620mm			490×300×920mm				
重量	13.2kg			17.3kg			20.8kg			47.5kg	

标准配置

主机	1个
----	----