



ISH-B-HRC30



ISH-B-HV700

- 符合JJG硬度块国家计量检定规程
- 带生产厂检验证书

技术参数

型号	硬度类型	规格**	均匀度
ISH-B-HRC□□*	HRC	20, 25, 30, 35, 40, 45, 50, 55, 57, 60, 62, 64, 67, 70	0.2(>40HRC), 0.3(≤40HRC)
ISH-B-HRA□□*	HRA	56, 65, 71, 75, 78, 81, 83, 85, 87	0.3
ISH-B-HRB□□*	HRB	32, 42, 52, 62, 72, 82, 90, 95, 100	0.8(>50HRB), 1(≤50HRB)
ISH-B-HR15N□□*	HR15N	75, 80, 85, 87, 90, 92	0.6
ISH-B-HR30N□□*	HR30N	41, 50, 55, 60, 67, 73, 78, 81, 83	0.6
ISH-B-HR45N□□*	HR45N	23, 43	0.6
ISH-B-HR15T□□*	HR15T	78, 82, 87	1
ISH-B-HR30T□□*	HR30T	32, 38, 42, 52, 62, 72, 78	1
ISH-B-HRE90	HRE	90	1
ISH-B-HRM□□*	HRM	67, 100	1
ISH-B-HRL□□*	HRL	92, 118	1
ISH-B-HRR□□*	HRR	105, 123	1
ISH-B-HRF90	HRF	90	1
ISH-B-HRS90	HRS	90	1
ISH-B-HMV□□*	HMV(1, 0.1)	1600	2%(HV1)
	HMV(1, 0.1, 0.01)	40, 100, 200, 300, 400, 500, 600, 700, 800, 900	5%(HV0.1), 7(100HV0.1), 4(40HV0.1)
	HMV(0.1, 0.01, 0.001)	30(Au)	4(HV0.1)
ISH-B-HV□□*	HV(30, 1)	700, 800, 900, 1000	1.5%(>150HV), 2.2%(≤150HV)
	HV(10, 1)	40, 100, 150, 200, 300, 400, 500, 600	1.5%(>150HV), 2.2%(≤150HV)
ISH-B-UMV□□*	UMV(0.01, 0.002)	200, 500, 700, 900	10%(HV0.01)
ISH-B-HS□□*	HS	7, 20, 30, 40, 50, 60, 70, 80, 90, 95, 100	1.5(>70HS), 1.2(≤70HS)
ISH-B-HLE□□*	HLE	500, 600, 700, 800, 860	—
ISH-B-HLD□□*	HLD	520, 630, 730, 830, 880	—
ISH-B-HBW□□*	HBW(10/3000)	150, 180, 200, 250, 300, 350, 400, 450, 500, 550, 600	1.5%(>150HBW), 2.5%(150HBW)
	HBW(10/500)	100, 125	2.5%(125HBW), 3%(100HBW)

* □□为相应的硬度规格，例如型号ISH-B-HRC60表示规格为60HRC的硬度块

** 供货时的实际值可能略有不同