

中空棘轮机械扭矩扳手

- 棘轮头部更耐用
- 符合JJG扭矩扳子国家计量检定规程
- 符合DIN ISO 6789标准
- 符合ASME B 107.300标准
- 中空方榫上下切换, 可满足顺/逆时针操作
- 双视窗设计, 清晰的刻度窗
- 防滑手柄
- 推拉式锁紧装置, 操作方便



IST-43WM100C

技术参数

型号	扭矩范围	精度	分度值	方头尺寸(D)	长度	净重
IST-43WM25C	5~25N.m	±3%	0.2N.m	1/4"	328mm	840g
IST-43WM50C	10~50N.m		0.5N.m	3/8"	392mm	1000g
IST-43WM60C	10~60N.m		0.5N.m	3/8"	392mm	1000g
IST-43WM100C	20~100N.m		0.5N.m	1/2"	434mm	1100g
IST-43WM150C	30~150N.m		1N.m	1/2"	504mm	1250g
IST-43WM200C	40~200N.m		1N.m	1/2"	504mm	1250g
IST-43WM300C	60~300N.m		1.5N.m	1/2"	556mm	1400g
IST-43WM400C	80~400N.m		2N.m	1/2"	700mm	1970g
IST-43WM550C	100~550N.m	±3% (≤500N.m) ±4% (>500N.m)	3N.m	3/4"	924mm	3670g
IST-43WM750C	150~750N.m		5N.m	3/4"	1076mm	4100g
IST-43WM850C	200~850N.m		5N.m	3/4"	1207mm	4500g
IST-43WM1000C	200~1000N.m		5N.m	3/4"	1207mm	4670g
IST-43WM1500C	300~1500N.m		10N.m	1"	1765mm	6500g
IST-43WM2000C	400~2000N.m		10N.m	1"	1943mm	6800g